

that the spoil is jettisoned immediately after damage if—

- (1) The hull is designed so that—
  - (i) The complete separation is effected within two minutes even if the main power source is lost or the actuating means is damaged; and
  - (ii) The actuating means can be operated from the navigating bridge;
- (2) It is shown to the Commanding Officer, Marine Safety Center, either by calculations or by operational tests, that the hulls can separate sufficiently to allow the dredged material to dump without bridging; and
- (3) Asymmetrical jettisoning of the spoil is impossible.

#### DESIGN

#### § 174.335 Watertight doors.

(a) Each hopper dredge must have sliding watertight doors (Class 3) approved under § 170.270 of this chapter if the sill for the door is—

- (1) Installed below the bulkhead deck; and
  - (2) Less than 24 inches above the final waterline as shown by the calculations required by § 174.310 in each damage condition up to and including the maximum amount of assumed damage.
- (b) Each hopper dredge must have sliding watertight doors (Class 3) approved under § 170.270 of this chapter, or quick acting hinged watertight doors (Class 1) approved under the same subpart if the sill of the watertight door is—
- (1) Installed below the bulkhead deck; and
  - (2) Greater than 24 inches above the final waterline as shown by the calculations required by § 174.310 in each damage condition up to and including the maximum amount of assumed damage.

[CGD 76-080, 54 FR 36977, Sept. 6, 1989, as amended by CGD 95-072, 60 FR 50468, Sept. 29, 1995]

#### § 174.340 Collision bulkhead.

Each hopper dredge must have a collision bulkhead that is located not less than 5 percent of the length abaft of the forward perpendicular.

### Subpart J—Special Rules Pertaining to Dry Cargo Ships

SOURCE: CGD 87-094, 58 FR 17320, Apr. 1, 1993, unless otherwise noted.

#### § 174.350 Specific applicability.

This subpart applies to each new ship of 500 gross tons or over, as calculated by the International Convention on Tonnage Measurement of Ships, 1969, designed primarily for the carriage of dry cargoes, including roll-on/roll-off ships and integrated tug and barges (ITBs) when operating as a combined unit.

#### § 174.355 Definitions.

*New ship* means a ship:

- (1) For which the building contract is placed on or after February 1, 1992; or
- (2) In the absence of a building contract, the keel of which is laid or which is at a similar stage of construction on or after August 1, 1992; or
- (3) The delivery of which is on or after February 1, 1997; or
- (4) For which application for reflagging is made on or after February 1, 1997; or
- (5) Which has undergone a major conversion:
  - (i) For which the contract is placed on or after February 1, 1992; or
  - (ii) In the absence of a contract, the construction work of which is begun on or after August 1, 1992; or
  - (iii) Which is completed on or after February 1, 1997.

#### § 174.360 Calculations.

Each ship to which this subpart applies, must meet the minimum standard of subdivision and damage stability required for that ship by the International Convention for the Safety of Life at Sea, 1974, as amended, chapter II-1, part B-1. Compliance with the applicable requirements must be demonstrated by calculations and reflected in information on loading restrictions, such as a maximum height of the center of gravity (KG) or minimum metacentric height (GM) curve that is part of the stability information required by § 170.110 of this chapter and Regulation 25-8 of The International Convention for the Safety of Life at

§ 174.360

46 CFR Ch. I (10–1–98 Edition)

Sea, 1974, as amended, chapter II-1,  
part B-1.

# INDEX

## SUBCHAPTER S—SUBDIVISION AND STABILITY

EDITORIAL NOTE: This listing is provided for informational purposes only. It is compiled and kept up-to-date by the Coast Guard, Department of Transportation.

### A

*Part, Subpart, or Section*

#### Addresses:

Material incorporated by reference .....	170.015
Merchant marine technical offices .....	170.100
Aft peak bulkhead, passenger vessels .....	171.090
Alterations .....	170.001(b), 170.005
Auxiliary sailing vessels:	
Defined .....	170.055(a)
Large passenger vessels .....	171.055
Small passenger vessels .....	171.035
Weather criterion for .....	170.170(c)

### B

#### Ballast, fixed. (See Fixed ballast.)

#### Barges:

Deck cargo .....	Part 174, Subpart B
Definitions .....	170.055(b), (o), (q)
Large passenger .....	171.045
Oceanographic research .....	173.070
Small passenger .....	171.020
Tank. (See Tank barges.)	
Weather criterion for .....	170.160
Bulk cargo vessels, special requirements for .....	Part 172
Buoyancy:	
Air tanks .....	171.070(d), 171.095(c)
Foam flotation material .....	170.245
Internal .....	171.070(d), 171.095(c)
Standards of flooding .....	171.017

### C

#### Calculations:

Samples of, in stability booklet .....	170.110(d)
Submittal of .....	170.090
Stability text results .....	170.175(a)
Catamarans .....	171.035(b), 171.057
Center of gravity:	
Determination of .....	Part 170, Subpart F
During simplified stability test .....	171.030(c)(4)
Estimated position on tank vessels .....	170.200
In stability booklet .....	170.110(d)
Subchapter O barges .....	172.090(b)
Tanks .....	170.075(a)(5)
Virtual increase of .....	Part 170, Subpart I
Collision bulkhead:	

## 46 CFR (10–1–98 Edition)

Oceanographic research vessels .....	173.075, 173.085
Passenger vessels .....	170.040, 171.060, 171.065, 171.070, 171.085
Consumable liquids:	
Effect on stability calculations .....	170.285, 170.290
In lightweight .....	170.055(i)
Cranes:	
Data required .....	170.095
Requirements for vessels with .....	Part 173, Subpart B
Cross curves, required .....	170.090(b)(3)
Cross-flooding:	
Instructions to the Master .....	171.110(d)(13)
Liquefied gas carriers, system standards .....	172.195(g)
Passenger vessels, system standards .....	171.080(e)
Subchapter O tankships, system standards .....	172.150(g)

## D

Damage stability:	
Liquefied gas carriers, local damage .....	172.205
Liquefied gas carriers, major damage .....	172.170
MODU's, standards for .....	174.065
Nautical school ships, standards for .....	173.055, 173.080
Nuclear powered vessels, standards for .....	174.120
Oceanographic research vessels, standards for .....	173.080
Oil tankers, standards for .....	172.065
OTEC facilities, standards for .....	174.155
Passenger vessels:	
Cockpits .....	171.145(e)(3)
Types I and II .....	171.080
Types III .....	171.082
Well decks .....	171.150(b)(2)
Subchapter D tank barges carrying cargoes other than oil .....	172.050
Subchapter O barges, standards for .....	172.103
Subchapter O tankships, standards for .....	172.133
Dangerous cargoes .....	Part 172, Subparts E and F
Dead covers:	
Oceanographic research vessels, required .....	173.085(k)
Passenger vessels, required .....	171.117, 171.119(a)(2), 171.122(g)
Deadweight surveys .....	170.175(c)
Deck cargo barges. (See Barges.)	
Definitions:	
Concerning a vessel .....	170.055
General terms .....	170.050
Pertaining to lifting .....	173.010
Pertaining to liquefied gas carriers .....	172.160
Pertaining to MODU's .....	174.035
Pertaining to passenger vessels .....	171.010
Pertaining to Subchapter O tankships .....	172.127
Discontinuous bulkhead deck, passenger vessels .....	171.015(c)
Discontinuous weather deck .....	170.170(b)
Double bottoms, passenger vessels:	
Manholes in .....	171.108
Permeability of .....	171.066(b)(4)
Required .....	171.105
Watertight floors in .....	171.109
Wells in .....	171.106
Downflooding:	
Angle .....	170.055(f)

## Index, Parts 170–174

Deck cargo barges.....	174.015
Defined (except MODU's) .....	170.055(e)
Lifting vessels .....	173.020(b)
Liquefied gas carriers .....	172.195
Mobile offshore drilling units (MODU's):	
Considered.....	174.045
Defined.....	174.035(b)
Oil tankers .....	170.055(f)
Sailing passenger vessels .....	171.055
Subchapter O barges .....	172.090
Subchapter O tankships .....	172.150
Tugboats and towboats .....	174.145
Vessels of unusual proportion and form .....	170.173
Vessels which tow .....	173.095
Draft marks .....	170.075(a) (6), 170.180(e)
Drainage of weather decks.....	Part 171, Subpart H
Deck cargo barges .....	Part 174, Subpart B

## E

Equalization. (See Cross-flooding.)	
Equivalent plane bulkhead, passenger vessels:	
Defined.....	171.010(c)
Required:	
Type I subdivision .....	171.067(f)
Type II subdivision.....	171.073(c)
Equivalents.....	170.010
Estimated lightweight vertical center of gravity.....	170.200
Existing vessels .....	170.001(b)

## F

Ferry:	
Collision bulkheads .....	171.040(d), 171.060(d)
Defined .....	171.010(d)
Intact stability during loading.....	171.030(g)
Fixed ballast.....	170.055(i), 170.110(d) (14), 170.235
Floodable length:	
Curves required.....	170.090(b) (4)
Defined.....	171.010(e)
Passenger vessels:	
Simplified—small passenger vessels .....	171.043(a)
Standards, Type I .....	171.065
Standards, Type II .....	171.070
Standards, Type III .....	171.075
Floors, watertight—in double bottoms.....	171.109
Foam flotation .....	170.245, 171.070(d), 171.095(c)
Foreign vessels .....	170.001(a) (2)
Freeboard:	
Allowable heeling limits, general .....	170.170(a), 171.030(e)–(h)
Passenger vessels, effective .....	171.043
Freeing ports:	
Minimum Area.....	171.150
Required .....	171.135
Free surface:	
Instructions concerning:	
Counterballasting .....	170.125(b) (1)
Stability booklet .....	170.110(d) (6)

## 46 CFR (10–1–98 Edition)

Subchapter O tank barges, assumption .....	172.087(b)
Treatment of, general .....	Part 170, Subpart I

### G

Grain in bulk.....	170.098, Part 172, Subpart B
“Grandfathering” .....	170.001(b)

### H

Hazardous liquids .....	Part 172, Subparts E, F
Hopper barges:	
Subchapter D cargoes other than oil .....	172.050
Subchapter O cargoes .....	172.100, 172.110
Hydrostatic curves (curves of form), required .....	170.075(a)(3), 170.100(d)(4)

### I

Inclining experiments. ( <i>See</i> Stability test.)	
Incorporation by reference:	
General .....	170.015
IMO Resolution A.265(VIII) .....	170.135, 171.075, 171.082
MIL-P-21929B.....	170.245(b)(9)
Intact stability:	
Deck cargo barges.....	174.015, 174.020
Large passenger vessels:	
Catamarans .....	171.057
Passenger heel.....	171.050
Sailing.....	171.055
Lifting vessels.....	173.020, 173.025
Liquefied gas carriers .....	172.165
Mobile offshore drilling units (MODU's) .....	174.045
Passenger vessels:	
Cockpits .....	171.145(e)(1)
Well decks .....	171.150(b)(2)
Small passenger vessels:	
General.....	171.030
Sailing.....	171.035
Subchapter O barges .....	172.090, 172.095
Tugboats and Towboats .....	174.145
Vessels of unusual proportion and form .....	170.170(d), 170.173
Weather Criterion.....	170.160, 170.170
International voyage:	
Passenger vessels:	
Aft peak bulkhead required .....	171.090(a)
Defined .....	171.010(g), (1)
Double bottoms required for .....	171.105(a)
Shaft tunnels .....	171.100(a)
Special considerations .....	171.068
Standards .....	171.045
Subdivision requirements .....	170.265(d)(1)
Watertight door requirements.....	170.265(d)(1)

### L

Large Passenger vessels .....	Part 171, Subpart C
Lifting:	
Data submittal requirements .....	170.095
Operating information requirements.....	170.125

## Index, Parts 170–174

Standards.....	Part 173, Subpart B
Lightweight:	
Defined .....	170.055(i)
Information required, stability booklet .....	170.110(d)(1)
Determination of .....	Part 170, Subpart F
Lines drawing required.....	170.075(a)(2), 170.180(a)
Liquefied flammable gas, barges.....	Part 172, Subpart C
Liquefied gas carriers .....	Part 172, Subpart G
LNG Carriers. (See Liquefied gas carriers.)	
Load line:	
Certificate, stability information on.....	170.110(e), 170.120(b)
Length, defined.....	170.055(h)(5)
Locks required:	
Cargo space watertight doors .....	170.275(b)
Port lights below the bulkhead deck.....	171.116(f)(4)

## M

Machinery space bulkhead, passenger vessels .....	171.095
Main transverse watertight bulkhead.....	170.055(j)
Manholes, passenger vessels:	
Double bottoms.....	171.108
Prohibited locations.....	171.111(h)
Margin line:	
Passenger vessels:	
Air tankage or internal buoyancy .....	171.070(d)(2)
Dead covers required on port lights, below.....	171.117(a)
Location of.....	171.015
Location of openings .....	171.111(f), (g)
Openings in trunks.....	171.113(c)(2)
Stepped bulkheads .....	171.067(b)(3)
Submergence of.....	171.017, 171.080(d)(3), 171.100(b)
Volume below .....	Tables 171.065(a), 171.066, 171.068
Volume of passenger spaces above .....	171.065(b)
Watertight integrity above .....	Part 171, Subpart G
Test head:	
Form flotation material .....	170.245(b)(3)
Watertight doors.....	170.270(b)
Military specifications, MIL-P-21929B.....	170.015(b), 170.245(b)
Mobile offshore drilling units (MODU's):	
Operating information required.....	170.130
Stability information required.....	170.110(a)
Standards for .....	174.005(b), Part 174, Subpart C

## N

Nautical school ships, standards .....	171.001(b), 173.001(b), Part 173, Subpart C
Nuclear powered vessel, standards .....	171.001(b), 174.005(c), Part 174, Subpart D

## O

Oceanographic vessel, standards .....	171.001(b), 173.001(c), Part 173, Subpart D
Oil in bulk, standards for vessels carrying .....	172.005(c), Part 172, Subpart D
Openings:	
Closed by weathertight covers:	
Liquefied gas carriers.....	172.195
Mobile offshore drilling units .....	174.045(c)
Oil tankers.....	172.065(g)

## 46 CFR (10–1–98 Edition)

Subchapter O tankships .....	172.150
Downflooding through:	
General .....	170.055(e), (f)
Mobile offshore drilling units .....	174.035(b), 174.065(a)
Subchapter O barges .....	172.090(d)
Sailing passenger vessels .....	171.055(f)
Mobile offshore drilling units:	
Closures for .....	174.100
Watertight, closed automatically .....	174.015(b)
Watertight, closed rapidly .....	174.045
Passenger vessels:	
Cockpit openings .....	171.145(a)(2)
Collision bulkhead .....	171.085
Effect on effective freeboard .....	171.043(b)
Special consideration, exposed weather decks .....	171.122(f)
Vessel sides .....	Part 171, Subpart F
Watertight bulkheads .....	Part 171, Subpart E
Watertight, closed automatically:	
Mobile offshore drilling units .....	174.015(b)
Towing vessels .....	173.095(e)
Operating manual .....	170.130
OTEC facilities .....	174.005(e), Part 174, Subpart F

## P

Passenger vessels, standards .....	Part 171
Penetrations. (See Openings.)	
Permeability	
Calculation of, Type I subdivision .....	171.066
Damage stability:	
Liquefied gas carriers .....	172.185
Mobile offshore drilling units .....	174.090
Oil tankers .....	172.065(f)
Passenger vessels .....	171.080(c)
Subchapter O tankships .....	172.140
Defined .....	170.055(k)
Uniform average permeability:	
Type I subdivision .....	Table 171.068
Type II subdivision .....	171.072
Plans:	
Approval:	
General .....	Part 170, Subpart C, 170.180
Required .....	170.075
Specific .....	170.093
Submittal of .....	170.100, 170.180
Port lights .....	171.116

## R

Repairs:	
General .....	170.001(b), 170.005
In way of fixed ballast .....	170.235(b)
Roll stabilization tanks .....	170.295
Rudders, towline pull criterion .....	173.095

## S

Sailing vessels:



## Index, Parts 170–174

Defined.....	170.055(a), (1)
Intact stability standards:	
Catamarans .....	171.057
Large passenger vessels.....	171.055
Small passenger vessels .....	171.035
Weather criterion .....	170.170(c)
School ships. (See Nautical school ships.)	
Shaft power, towline pull criterion .....	173.095
Shaft tunnels:	
On passenger vessels .....	171.100, 171.106(c)
Watertight doors in .....	170.260(d)
Short international voyages, vessels on:	
Class 3 doors .....	170.265(d)(1)
Defined.....	171.010(1)
Double bottoms not required.....	171.105(h)(2)
Special considerations.....	171.068
Side ports, passenger vessels .....	171.118
Sister vessel, stability test dispensed with .....	170.175(c)
Small passenger vessels, standards.....	Part 171
Stability booklets:	
Contents of .....	170.110
Lifting vessels, additional information .....	170.125
Submission and approval required.....	170.080
Vessels with Type III subdivision, additional information.....	170.135
Stability letters:	
In lieu of stability booklet .....	170.110(e)
Required .....	170.120
Stability test:	
General .....	170.175
Information required before test .....	170.085
Plans and information required at test .....	170.180
Preparations for test .....	170.185
Simplified test, small passenger vessels.....	171.030, 171.035
Test procedure, modification of.....	170.190
Stern tubes, passenger vessels .....	171.100
Subdivision:	
Nuclear powered vessels, requirements .....	174.115, 174.125
Oceanographic vessels .....	173.075, 173.085
Passenger vessels:	
Additional requirements .....	Part 171, Subpart D
Calculations:	
Type I.....	171.065, 171.066, 171.067, 171.068
Type II.....	171.070, 171.072, 171.073
Type III .....	171.075
Requirements, large passenger vessels.....	171.060
Requirements, small passenger vessels.....	171.040
Trunks, effect of.....	171.113(b)(3)
Subdivision load line (draft), passenger vessels:	
Cockpits .....	171.145(e), (f)
Dead cover locations .....	171.117(b)
Deepest, defined.....	171.010(b)
Openings in hull, small passenger vessels .....	171.119(a)
Port light locations .....	171.116(b)(2)
Transverse damage extent, relationship to .....	171.065(h)(2), Table 171.080(a)
Ventilators and side port locations .....	171.118(c)
Superstructures:	
Buoyancy of:	

## 46 CFR (10–1–98 Edition)

Liquefied gas carriers .....	172.195(e)
Oil tankers.....	172.065(h)
Subchapter O tankships .....	172.150
Integrity of, mobile offshore drilling units .....	174.100(b)
Points of downflooding in:	
General.....	170.055(e)
Mobile offshore drilling units .....	174.035(b)(1)
Port lights in, oceanographic vessels.....	173.085(k)
Windage area of, small passenger vessels .....	171.030(d)

## T

Tank barge:	
Assumed center of gravity for .....	170.200(b)(2)
Carrying oil in bulk .....	Part 172, Subpart D
Carrying Subchapter D cargoes other than oil .....	Part 172, Subpart C
Carrying Subchapter O cargoes.....	Part 172, Subpart E
Defined .....	170.055(o)
Tank vessel:	
Assumed center of gravity .....	170.200
Defined .....	170.055(n)
Standards for .....	Part 172, Subparts C, D, E, F, G
Tests:	
Foam flotation material.....	170.245
Passenger vessels:	
Operational, sailing vessels .....	171.035(f)
Simplified stability test, small passenger vessels.....	171.030, 171.035
Stability.....	170.085, Part 170, Subpart F
Watertight doors.....	170.270
Towboats. (See Towing.)	
Towing, standards for... 173.001(d), Part 173, Subpart E, 174.005(d), Part 174, Subpart	E
Towline pull criterion.....	173.095
Tugboats. (See Towing.)	

## U

Unusual proportion and form, vessels of.....	170.173
--	---------

## V

Ventilators, automatic—passenger vessels.....	171.118
---	---------

## W

Watertight bulkheads:	
Doors, standards for.....	171.122, 171.124, Part 170, Subpart H
Liquefied gas carriers .....	172.175, 172.195
Mobile offshore drilling units .....	174.080, 174.085
Oceanographic vessels, ducts through .....	173.085(o)
Oil tankers.....	172.065
Passenger vessels:	
Above weatherdeck .....	171.122
Large passenger vessels, requirements .....	171.065, 171.067, 171.068, 171.070, 171.073
Machinery space.....	171.095
Penetrations of.....	Part 171—Subpart E
Small passenger vessels, requirements .....	171.040, 171.043
Watertight floors .....	171.109
Subchapter D barges not carrying oil.....	172.050

## Index, Parts 170–174

Subchapter O barges .....	172.104
Subchapter O tankships.....	172.133(d), 172.150
Watertight doors. ( <i>See</i> Watertight bulkheads.)	
Weather criterion.....	Part 170, Subpart E
Wind heeling moment:	
Small passenger vessels.....	171.030(d), 171.035(g)
MODU's.....	174.035(b)(2), 174.045, 174.055, 174.065(a)(2), 174.100(d)(2)